

3D Digital Design & Development LTD  
58/60 Edward Road  
Tri-Bec House  
New Barnet  
EN4 8AZ  
020 8440 7060



## **Tempulog 4x4**

### **Datasheet**

**Temperature Monitoring Any Time, Any Place**  
**Technology Working For You**

---

## Tempulog 4x4 technical specifications

### Specifications

- Part Number T4X4
- 4 Channel PT100 Class A 4 wire input **or** 4 channel thermocouple type K
- Optional local ambient temperature and relative humidity
- Resolution: 0.1C
- Accuracy: +/-0.3C
- Operating range: -150C to 300C P100 or -100C to 500C type K thermocouple
- 4 Channel 4-20 mA, 15 volts supply available
- 4 Volt-free relay contacts inputs
- LCD display & Joystick Control
- Change over alarm relay
- Alarm buzzer and ultra-bright alarm LED
- Power outage SMS
- Daily system Ok SMS
- Built-in GPRS connection
- Built-in SMS and Email alarms
- Continuous logging without mains power
- Ethernet connection
- 24 hours battery backup operation
- Dimension: HWD 150 mm x 245 mm x 42 mm
- Weight: 1.25 kg
- Wall mounted steel enclosure

### Communication:

The Tempulog 4x4 has the following communication options

Ethernet connection with Server/Client options

Built GPS & GPRS modem for remote Internet connection via the mobile network

Optional USB connection to host PC or Laptop